



TILE AND STONE SURFACE PROTECTION

CLEANING, SEALING AND AFTERCARE SOLUTIONS

VALVERDI PORCELAIN CLEANING AND AFTER CARE GUIDE



Valverdi porcelain floor tiles are extremely hard wearing. The external tiles have a depth of 20mm and a textured anti-slip finish making them an ideal choice for both domestic and heavily trafficked commercial areas. The following is a guide for initial cleaning (build clean), general cleaning and aftercare with the option of sealing to assist with grout release (fixing method 3) from the textured surface and to help ease the removal of daily dirt and grime including rubber sole marks.

CLEANING AFTER GROUTING

USE LTP GROUT STAIN REMOVER
Suitable for interior & exterior use

Valverdi fixing method 3: Fixing onto reinforced concrete with grouted joints.

Use for build cleaning after laying and grouting. Removes cement residues, builder's dirt /grime.

For best results apply directly to the surface and agitate immediately. Rinse well by hosing external surfaces. Internal surfaces use a sponge and water. Leave surfaces to dry.



SEALING (optional 20mm outdoor only)

USE LTP MATTSTONE (minimal change to original appearance)

Sealing surfaces before grouting will help with grout release. Removal of surface marks from organic matter, bird defecation, marks from shoes and general dirt and grime are also made easier to remove.

Apply a light coat to the surface using a foam roller, sealant applicator pad or paint brush. Leave to dry for 4 hours before allowing traffic or grouting the joints.

For best results; sealed surfaces should be kept dry for a minimum of 24 hours.



ALGAE & MILDEW REMOVAL (damp areas)

USE LTP MOULDEX PAVING CLEANER

Ideal for use in damp areas under shade where the control of surface algae growth is necessary.

Apply to the affected areas. Leave for up to 1 hour (heavily contaminated surfaces can be left longer). Scrub and rinse.



AFTER CARE (indoor - out)

USE LTP PORCELAIN FLOOR TILE CLEANER
Domestic and Commercial
PH neutral formula effectively cleans surfaces without leaving a film or removing protective coatings.

Dilute 1 capful of Porcelain floor tile cleaner per litre of water. Mop surfaces and leave to dry.

Rotary scrubber dryers can be used over larger areas, in which case dilute cleaner 1: 40 with water. This product does not require rinsing



INTENSIVE CLEANING

USE LTP GRIMEX (heavy duty grime remover)
Domestic and Commercial

For the removal of scuff marks from rubber soles, ground in dirt and grime in both domestic and commercial areas subjected to high levels of traffic. Clean every 6 months.

Dilute 1 part Power Stripper with 3 parts water. Apply the dilute solution to the surface of the tiles and grout joints. Agitate with an abrasive pad, scrubbing brush or machine, wipe away the released dirt and grime and then rinse thoroughly with a separate pot of clean fresh water or extract using a scrubber dryer machine. On really dirty floors and grouting this process may need to be repeated.



HEALTH & SAFETY

MSDS and technical data sheets for all products are available to download from the LTP website.
www.ltp-online.co.uk

This information is offered without guarantee. The material should be used so as to take account of the local conditions and the surfaces to be treated. In case of doubt, the product should be tried out in an inconspicuous area



Tone Estate, Milverton road, Wellington, Somerset TA21 0AN
Tel: 01823 666213 Fax: 01823 665685 Email: info@ltp-online.co.uk
technical@ltp-online.co.uk www.ltp-online.co.uk

